



PRESTONETT® Interior/Exterior Ready Mixed Wood Filler

GENERAL INFORMATION

DESCRIPTION

- Ready Mixed wood filler

INTENDED USE

- Interior/Exterior
- Suitable for use on most types of wood
- Ideal for repairs to doors, window frames skirting boards & floor boards

PRODUCT ADVANTAGES

- ✓ Flexible
- ✓ Fibre glass reinforced
- ✓ Quick drying
- ✓ Easy to sand
- ✓ Stain, varnish or paint



1

PRESTONETT®



N° 1.300



PRESTONETT®

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue: July 2014

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

▶▶ PRESTONETT® Interior/Exterior Ready Mixed Wood Filler

TECHNICAL DATA

◉ PRESENTATION	Ready Mixed Filler
◉ COMPONENTS	Acrylic Polymers
◉ DENSITY	1,5 +/- 0.1
◉ pH	7,5 - 8,5
◉ COLOUR	White, Natural, Medium, Dark
◉ OPEN TIME AT 20°C	Unlimited
◉ WAITING TIME BEFORE OVERCOATING	1-4 hours depending on type of substrate, temperature, humidity and thickness of application
◉ CLASSIFICATION	NF T 36-005 - Famille IV, classe 3
◉ HEALTH AND SAFETY	Safety data sheet available on request or from www.quickfds.com
◉ PACKAGING	125 ml tube
◉ STORAGE	12 months in original sealed packaging, protected from frost, heat and moisture

USE

◉ DILUTION	Ready mixed
◉ APPLICATION	Massage tube before application. Work the filler in to the repair and leave slightly proud for sanding. For deep repairs fill in two or more layers. Once dry sand and then stain, varnish or paint. <ul style="list-style-type: none">• <i>Equipment</i> Spatula or filling knife• <i>Conditions</i> Do not apply at temperatures of below +5°C or above +30°C, or at a relative humidity of above 65% HR (hygrometry rate)• <i>Equipment cleaning</i> With water before completely dry
◉ SPECIAL RECOMMENDATIONS	Exterior use: The filler must be over coated with a weather proof stain/varnish or paint
◉ APPLICATION THICKNESS	5mm maximum per layer
◉ SUBSTRATES	Most types of wood, chipboard, plywood etc... DO NOT APPLY ON DAMP WOOD Substrates must be clean, dry and free from dust, grease & wax. Metallic parts must be primed
◉ OVERCOAT	Stain, varnish or paint