

## PRODUCT DATA

## PARACEM DECO

### DESCRIPTION

Waterborne acrylic paint for high-quality indoor works.

### MAIN PROPERTIES

Excellent flow - good mechanical resistance against rubbing - smooth mat aspect - high covering power – tendency not to overlap.

### RECOMMENDED USES

Decorative and mat finishing for indoor walls and ceilings. Applicable on most substrates (plaster, bricks, concrete, etc.) as well in private as in public buildings.

### TECHNICAL DATA

Appearance:	Matt (gloss 60°: 2 - 3% / 85°: 2 - 3%)
Colour:	White + Mathymix / ColourShop
Density:	1.40 ± 0,02 g/cm <sup>3</sup> (white)
Solids Content:	In volume: 34 ± 1% (white) In weight: 51,5 ± 1% (white)
Recommended film thickness:	Wet film: ± 140 micron (consumption: 7 m <sup>2</sup> /l ) Dry film: ± 50 micron (consumption: 7 m <sup>2</sup> /l )
Flashpoint:	Not flammable
VOC-content:	30 g/l max.
Ready-for-use mixture:	30 g/l max.
Category:	A/a
EU Limit values:	75 g/l (2007) / 30 g/l (2010)

<b>Drying times</b>	20°C/50% r.h.
To touch:	30 minutes
To recoat:	1 hour
Full hardness	± 2 days

### Coverage

Theoretical:	7 - 10 m <sup>2</sup> /l per coat
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

Old cleaned layers in good condition and light porous substrates may be recoated directly with Paracem Deco.

Very porous substrates, smooth plaster and water-resistant plasterboard are to be impregnated first with a coat of the 1/1 mixture Pegafix + Paracem Deco with a consumption of 12 m<sup>2</sup>/l per coat.

Nicotine stains must be isolated first with Pegaprim Isofix, Pegamat Aqua or Pegamat RL.

Old damp spots must be isolated with Pegamat RL or Pegaprim Isofix.

Unpainted woodwork must be treated appropriately first and a priming coat must be applied (e.g. Fassiprim or Pegaprim Xpress).

Metal objects without rust spots are to be pre-treated with Pegalink, Pegaprim Xpress or Galvaprim.

On glass fibre, apply preferably first a coat of Paracem Deco Soft or Paracem Deco Satin before finishing with a coat of Paracem Deco.

### DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

**Rust-Oleum Netherlands B.V.**  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum France S.A.S**  
11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum UK Ltd.**  
Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

## PRODUCT DATA

## PARACEM DECO

### APPLICATION & THINNING

- Brush: Apply undiluted.
- Roller: Apply undiluted.
- Air-atomised spray: Possible. If necessary dilute with water.
- Airless spray: Nozzle: 013 - 019 / Pressure: 160 - 200 bars.
- Cleanup: Water.

### APPLICATION CONDITIONS

> 5°C, < 80% R.H.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

#### Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

#### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum UK Ltd.

Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)