



PRESTONETT® Interior Ready Mixed Joint Filler

GENERAL INFORMATION

DESCRIPTION

- Ready Mixed Joint Filler

INTENDED USE

- Interior
- For taping and jointing plasterboards

PRODUCT ADVANTAGES

- ✓ Excellent adhesion and minimal shrinkage
- ✓ For all stages of plasterboard jointing
- ✓ Easy to trowel
- ✓ Easy to sand
- ✓ White



1

PRESTONETT®



N° 1.250



1

PRESTONETT®

This data sheet supersedes and replaces any prior sheet relating to the same products.

Date of issue: September 2012

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.



PRESTONETT® Interior Ready Mixed Joint Filler

TECHNICAL DATA

◉ PRESENTATION	Ready Mixed Filler
◉ COMPONENTS	Acrylic copolymers Selected minerals extenders and admixtures
◉ DENSITY	1.7 ± 0.1
◉ pH	8 ± 1
◉ COLOUR	White
◉ WORKING TIME AT 20°C	Unlimited
◉ WAITING TIME BEFORE OVERCOATING	Once completely dry
◉ CLASSIFICATION	NF EN 13 963 - Class 3A
◉ REACTION TO FIRE	EUROCLASS - A2 - s1, d0 Certificate available on request
◉ HEALTH AND SAFETY	Safety data sheet available on request or from www.quickfds.com
◉ PACKAGING	7 kg bucket
◉ STORAGE	6 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C) and moisture

USE

◉ DILUTION	Ready mixed
◉ APPLICATION	
• <i>Equipment</i>	Trowel or blade
• <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +30°C, or at a relative humidity of above 65% HR (hygrometry rate)
• <i>Equipment cleaning</i>	With water before completely dry
◉ APPLICATION THICKNESS	3 mm
◉ AVERAGE CONSUMPTION	0,350 kg/lm
◉ SUBSTRATES	Plasterboard Substrates must be hard, cohesive, clean, sound and dry
◉ OVERCOAT	Fibreglass cloth, interior conventional paint, wallpaper and plaster