



# SAFETY DATA SHEET

## EPOXY Shield® Garage Floor Coating (Base)

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- Product name and/or code** : EPOXY Shield® Garage Floor Coating (Base)  
Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands  
NV Martin Mathys, Kolenbergstraat 23, B-3545 Zelem, Belgium
- Emergency phone number** : Rust-Oleum: +31(0)165-593636; Fax +31(0)165-593600  
Martin Mathys: +32(0)13-460200; Fax +32(0)13-460201
- e-Mail address of person responsible for this SDS** : rpmeurohas@ro-m.com
- Product use** : Paint. Base for 2-component paint.

### 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

- Classification** : R43  
N; R51/53
- Human health hazards** : May cause sensitization by skin contact.
- Environmental hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name	CAS #	%	EU no.	Classification
polyethylenepolyamines	-	10 - 25	268-626-9	N; R50/53 [1]
2-(propyloxy)ethanol	2807-30-9	2.5 - 5	220-548-6	Xn; R21 [1] Xi; R36
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	1 - 2.5	220-666-8	Xn; R21/22 [1] C; R34 R43 R52/53
m-phenylenebis(methylamine)	1477-55-0	1 - 2.5	216-032-5	Xn; R20/22 [1] C; R34 R52/53
naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	0 - 1	265-185-4	R10 [1] [2] Xn; R65 R66 N; R51/53
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

### 4. FIRST AID MEASURES

#### First aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

## 5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

## 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Due to the organic solvents content of the preparation:  
Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**Note:** see section 8 for personal protective equipment and section 13 for waste disposal.

## 7. HANDLING AND STORAGE

- Handling** : Due to the organic solvents content of the preparation:
- Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.
- Keep container tightly closed. Keep away from heat, sparks and flame.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Observe label precautions. Do not store below the following temperature: 4°C (39.2°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.
- Keep away from: oxidizing agents, strong alkalis, strong acids.  
No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

### Ingredient name

naphtha (petroleum), hydrodesulfurized heavy

### Occupational exposure limits

**EH40-WEL (United Kingdom (UK), 6/2005).**

STEL: 850 mg/m<sup>3</sup>, (as turpentine (150 ppm)) 15 minute(s). Form: Vapor

TWA: 566 mg/m<sup>3</sup>, (as turpentine (100 ppm)) 8 hour(s). Form: Vapor

### Exposure controls/personal protection

- Occupational exposure controls** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection** : In case of insufficient ventilation, wear suitable respiratory equipment.  
Recommended: organic vapor filter (Type A) (EN 140).
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
>8 hours (breakthrough time): PVC or nitrile rubber (EN 374)  
*Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.*
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.  
Recommended: Wear safety glasses with side shields to prevent eye contact. (EN 166)
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Wear overalls or long sleeved shirt. (EN 467)
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : Liquid.
- Odor** : Ammoniacal.
- Color** : Gray.
- Flash point** : Closed cup: >100°C (>212°F)
- Boiling point** : 301°C (573,8°F)
- Vapor pressure** : <2,7 kPa (<20 mm Hg)
- Vapor density** : <1 [Air = 1]
- Volatility %** : 59.7% (v/v), 45.1% (w/w)
- Relative density (kg/L)** : 1,32

## 10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine. May produce an allergic reaction.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
polyethylenepolyamines	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
2-(propyloxy)ethanol	LD50 Dermal	Rabbit	960 uL/kg	-
	LD50 Oral	Rat	3090 mg/kg	-
	LD50 Oral	Rat	3089 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine)	LD50 Dermal	Rabbit	2 gm/kg	-
	LD50 Oral	Rat	930 mg/kg	-
	LC50 Inhalation Gas.	Rat	700 ppm	1 hours
naphtha (petroleum), hydrodesulfurized heavy	LD50 Dermal	Rabbit	>3000 mg/kg	-
	LD50 Oral	Rat	>6500 mg/kg	-
	LC50 Inhalation Vapor	Rat	>14 mg/L	4 hours

**12. ECOLOGICAL INFORMATION**

There is no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 2 and 15 for details.

**Aquatic ecotoxicity**

Ingredient name	Result	Species	Exposure
2-(propyloxy)ethanol	Acute LC50 >91.3 mg/L	Daphnia - daphnia	96 hours
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Acute EC50 37.4 mg/L	Daphnia	24 hours
naphtha (petroleum), hydrodesulfurized heavy	Acute EC50 17.4 to 21.5 mg/L Fresh water Acute EC50 4 to 10 mg/L	Daphnia - Water flea - Daphnia magna - <24 hours Daphnia	48 hours 48 hours
	Acute IC50 10 to 100 mg/L Acute LC50 10 to 100 mg/L	Algae Fish	72 hours 96 hours

**Ecological information****Biodegradability**

**Conclusion/Remark** : This product has not been tested for biodegradation.

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
naphtha (petroleum), hydrodesulfurized heavy	-	100%; < 28 day(s).	-

**Bioaccumulative potential**

Ingredient name	LogP <sub>ow</sub>	BCF	Potential
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1.9	-	low
naphtha (petroleum), hydrodesulfurized heavy	>3	-	high

**13. DISPOSAL CONSIDERATIONS**

Do not allow to enter drains or watercourses.  
Dispose of according to all federal, state and local applicable regulations.



**European waste catalogue (EWC)** : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 15\* aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

**Hazardous waste** : Yes.

**14. TRANSPORT INFORMATION**

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.


**International transport regulations**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>ADR/RID Class</b>	3082 LQ	Environmentally hazardous substance, liquid, n.o.s. Limited quantity	9	III		<b>Limited quantity:</b> LQ7  <b>Remarks:</b> (≤ 5L: ) Limited Quantity - ADR/IMDG 3.4.6  ADR Tunnel Restriction Code: (E)
<b>IMDG Class</b>	3082 LQ	Environmentally hazardous substance, liquid, n.o.s. Limited quantity Marine pollutant ( polyethylenepolyamines )	9	III		<b>Emergency schedules (EmS):</b> F-A + S-E  <b>Marine pollutant (P)</b>  <b>Remarks:</b> (≤ 5L: ) Limited Quantity - ADR/IMDG 3.4.6
<b>IATA Class</b>	3082	Environmentally hazardous substance, liquid, n.o.s.	9	III	 	<b>Passenger and Cargo Aircraft</b> Quantity limitation: - Packaging instructions: 914

PG\* : Packing group

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

**15. REGULATORY INFORMATION**

<b>EU regulations</b>	: The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:
<b>Hazard symbol or symbols</b>	: 
<b>Risk phrases</b>	: Irritant, Dangerous for the environment R43- May cause sensitization by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Safety phrases</b>	: S29/35- Do not empty into drains; dispose of this material and its container in a safe way. S36/37- Wear suitable protective clothing and gloves. S61- Avoid release to the environment. Refer to special instructions/safety data sheet.
<b>Contains</b>	: 3-aminomethyl-3,5,5-trimethylcyclohexylamine
<b>VOC for Ready-for-Use Mixture</b>	: IIA/j. Two-pack reactive performance coatings for specific end use such as floors. EU limit values: 140g/l (2007) 140g/l (2010.) This product contains a maximum of 53 g/l VOC.
<b>Europe inventory</b>	: Not determined.
<b>Other EU regulations</b>	
<b>CN code</b>	: 3209 90 00

**16. OTHER INFORMATION**

<b>Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)</b>	: R10- Flammable. R21- Harmful in contact with skin. R20/22- Harmful by inhalation and if swallowed. R21/22- Harmful in contact with skin and if swallowed. R65- Harmful: may cause lung damage if swallowed. R34- Causes burns. R36- Irritating to eyes. R43- May cause sensitization by skin contact. R66- Repeated exposure may cause skin dryness or cracking. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---	--

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

☑ Indicates information that has changed from previously issued version.

**Notice to reader**

*The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties. ©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.*